

AQUAPANEL® Fugenspachtel - grau

Safety Data Sheet

according to Regulation (EU) 2015/830

Issue date: 2016/12/19 Revision date: 2020/07/09 Version: 2.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : AQUAPANEL® Fugenspachtel - grau

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use, Consumer use
Use of the substance/mixture : Wall plaster

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Knauf Gips KG
Am Bahnhof 7
97346 Iphofen - Deutschland
T +49 932331-0 - F +49 932331-277
zentrale@knauf.de - www.knauf.de

E-mail address of competent person responsible for the SDS : sds-info@knauf.de

Technical information

Technical information service
T +49 (0)9001/31-1000 (see section 16)
knauf-direkt@knauf.de

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315
Eye Dam. 1 H318
STOT SE 3 H335

Full text of hazard classes and H-statements : see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Extra labelling to display Extra classification(s) to display

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP) : Danger

Hazardous ingredients : calcium hydroxide; Portland cement; Flue Dust

AQUAPANEL® Fugenspachtel - grau

Safety Data Sheet



according to Regulation (EU) 2015/830

Hazard statements (CLP)	: H315 - Causes skin irritation. H318 - Causes serious eye damage. H335 - May cause respiratory irritation.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P261 - Avoid breathing dust. P280 - Wear protective gloves, eye protection, protective clothing. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P313 - Get medical advice/attention.
Extra phrases	: In case of proper storage in a dry location low in chromate content for at least 12 months from date of manufacture.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
quartz, conc respirable crystalline silica<1%	(CAS-No.) 14808-60-7 (EC-No.) 238-878-4	>30 - <40	Not classified
Portland cement	(CAS-No.) 65997-15-1 (EC-No.) 266-043-4	25 - 35	Skin Sens. 1, H317 Eye Dam. 1, H318 Skin Irrit. 2, H315 STOT SE 3, H335
calcium hydroxide	(CAS-No.) 1305-62-0 (EC-No.) 215-137-3 (REACH-no) 01-2119475151-45, 01-2119475325-36	5 - <10	Eye Dam. 1, H318 Skin Irrit. 2, H315 STOT SE 3, H335
Flue Dust	(CAS-No.) 68475-76-3 (EC-No.) 270-659-9 (REACH-no) 01-2119486767-17	>0,02 - <1,5	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1B, H317 STOT SE 3, H335

Comments : Low in chromate according to EU-Regulation 1907/2006 (REACH).
Product contains chromate reducing agent. Therefore, the cement/binder contains less than 0,0002% of water-soluble Chromium(VI). If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the present reducing agent can be diminished prematurely, and the cement/binder can become skin sensitizing (H317 or EUH203, respectively).

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Take off contaminated clothing. Wash contaminated clothing before reuse.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Rinse and then wash skin thoroughly with water and soap. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth thoroughly with water. Immediately give plenty of water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause respiratory irritation.
Symptoms/effects after skin contact : Irritation.
Symptoms/effects after eye contact : Serious damage to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.
Unsuitable extinguishing media : Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not combustible.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear personal protective equipment. Keep public away from danger area. Evacuate personnel to a safe area.

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing dust. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Avoid creating or spreading dust.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing dust. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

calcium hydroxide (1305-62-0)		
EU	Local name	Calcium dihydroxide
EU	IOELV TWA (mg/m ³)	1 mg/m ³ (Respirable fraction)
EU	IOELV STEL (mg/m ³)	4 mg/m ³ Respirable fraction
quartz, conc respirable crystalline silica<1% (14808-60-7)		
EU	Local name	Silica crystalline (Quartz)
EU	IOELV TWA (mg/m ³)	0,1 mg/m ³ (Respirable fraction)
EU	Notes	OEL limit below 0.05 mg/m ³ of respirable silica dust. (Year of adoption 2003)

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)			

Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Safety glasses			EN 166

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Dust mask	Type P2	Dust protection	EN 149



Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Ensure adequate ventilation, especially in confined areas. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powders.
Colour	: Grey.
Odour	: none to slight.
Odour threshold	: No data available
pH	: 11 – 13 Saturated solution

AQUAPANEL® Fugenspachtel - grau

Safety Data Sheet



according to Regulation (EU) 2015/830

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Water: 1650 mg/l
Partition coefficient n-octanol/water (Log Pow)	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: Product is not explosive.
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

Bulk density : 900 – 1000 kg/m³

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Flue Dust (68475-76-3)	
LD50 oral rat	> 1848 mg/kg bodyweight Animal: rat, Guideline: other:OECD 422
LD50 dermal rat	≥ 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	> 6,04 mg/l air Animal: rat, Guideline: OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class Method)

calcium hydroxide (1305-62-0)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	> 2500 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male / female, Experimental value, Dermal)

Skin corrosion/irritation : Causes skin irritation.
pH: 11 – 13 Saturated solution

Serious eye damage/irritation	: Causes serious eye damage. pH: 11 – 13 Saturated solution
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Portland cement (65997-15-1)	
LC50 fish 1	> 1000 mg/l (96 h, Pisces)

Flue Dust (68475-76-3)	
EC50 72h algae (1)	28,2 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)
EC50 72h algae (2)	22,4 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)

calcium hydroxide (1305-62-0)	
LC50 fish 1	50,6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	49,1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h algae (1)	184,57 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

Portland cement (65997-15-1)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

calcium hydroxide (1305-62-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

quartz, conc respirable crystalline silica<1% (14808-60-7)	
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

Portland cement (65997-15-1)	
Bioaccumulative potential	Bioaccumulation: not applicable.

calcium hydroxide (1305-62-0)	
Bioaccumulative potential	Not bioaccumulative.

quartz, conc respirable crystalline silica<1% (14808-60-7)	
Bioaccumulative potential	No bioaccumulation data available.

12.4. Mobility in soil

AQUAPANEL® Fugenspachtel - grau

Safety Data Sheet



according to Regulation (EU) 2015/830

Portland cement (65997-15-1)	
Ecology - soil	No (test)data on mobility of the substance available.
calcium hydroxide (1305-62-0)	
Ecology - soil	Adsorbs into the soil.
quartz, conc respirable crystalline silica<1% (14808-60-7)	
Ecology - soil	Low potential for mobility in soil.

12.5. Results of PBT and vPvB assessment

Component	
quartz, conc respirable crystalline silica<1% (14808-60-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
calcium hydroxide (1305-62-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Portland cement (65997-15-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code : 17 09 03* - other construction and demolition wastes (including mixed wastes) containing dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

- Overland transport

Not applicable

- Transport by sea

Not applicable

- Air transport

Not applicable

- Inland waterway transport

Not applicable

- Rail transport

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

This safety data sheet replaces the previous version of 2016/12/19. The following changes were made:

Other information

: Technical information service (see point 1):

A call to Knauf Direkt will be charged at 0.39 € per minute. Callers, the telephone numbers of whom are not saved in the Knauf Gips KG address database, e.g. private property owners or noncustomers, will pay 1.69 € per minute from the German network. Callers using mobile telephones will be charged according to the network provider and tariff.

Full text of H- and EUH-statements:

Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Knauf SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.