

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Rotkalk Filz 05

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Professional use, Consumer use  
Use of the substance/mixture : Plaster

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Knauf Gips KG  
Am Bahnhof 7  
97346 Iphofen - Deutschland  
T +49 932331-0 - F +49 932331-277  
[zentrale@knauf.de](mailto:zentrale@knauf.de) - [www.knauf.de](http://www.knauf.de)  
E-mail address of competent person responsible for the SDS : [sds-info@knauf.de](mailto:sds-info@knauf.de)

##### Technical information

Technical information service  
T +49 (0)9001/31-2000 (see section 16)  
[knauf-direkt@knauf.de](mailto:knauf-direkt@knauf.de)

#### 1.4. Emergency telephone number

No additional information available

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315  
Eye Dam. 1 H318  
STOT SE 3 H335

Full text of hazard classes and H-statements : see section 16

##### Adverse physicochemical, human health and environmental effects

No additional information available

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP] Extra labelling to display

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP) : Danger  
Hazardous ingredients : Portland cement; calcium hydroxide

# Rotkalk Filz 05

## Safety Data Sheet



according to Regulation (EU) 2015/830

Hazard statements (CLP)	: H315 - Causes skin irritation. H318 - Causes serious eye damage. H335 - May cause respiratory irritation.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P261 - Avoid breathing dust. P280 - Wear protective gloves, eye protection, protective clothing. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P313 - Get medical advice/attention.

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
calcium hydroxide	(CAS-No.) 1305-62-0 (EC-No.) 215-137-3 (REACH-no) 01-2119475151-45	< 20	Eye Dam. 1, H318 Skin Irrit. 2, H315 STOT SE 3, H335
Portland cement	(CAS-No.) 65997-15-1 (EC-No.) 266-043-4	< 10	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Comments : Low in chromate according to EU-Regulation 1907/2006 (REACH).  
The contained Portland cement is white cement.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Take off contaminated clothing. Wash contaminated clothing before reuse.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Rinse and then wash skin thoroughly with water and soap. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth thoroughly with water. Immediately give plenty of water. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.  
Unsuitable extinguishing media : Strong water jet.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Non combustible.  
Hazardous decomposition products in case of fire : Toxic fumes may be released.

#### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid breathing dust. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing dust. Avoid contact with skin and eyes. Wear personal protective equipment.  
Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

calcium hydroxide (1305-62-0)		
EU	Local name	Calcium dihydroxide
EU	IOELV TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> Respirable fraction
EU	IOELV STEL (mg/m <sup>3</sup> )	4 mg/m <sup>3</sup> Respirable fraction

#### 8.2. Exposure controls

# Rotkalk Filz 05

## Safety Data Sheet



according to Regulation (EU) 2015/830

### Appropriate engineering controls:

Ensure good ventilation of the work station.

### Hand protection:

Protective gloves

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
	Nitrile rubber (NBR)	6 (> 480 minutes)			

### Eye protection:

Safety glasses

Type	Use	Characteristics	Standard
Sealed safety goggles			EN 166

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Device	Filter type	Condition	Standard
Dust mask	Type P2	Dust protection	EN 149



### Environmental exposure controls:

Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powders.
Colour	: white / Grey.
Odour	: earthy.
Odour threshold	: No data available
pH	: 11 - 13 Saturated solution
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

# Rotkalk Filz 05

## Safety Data Sheet



according to Regulation (EU) 2015/830

### 9.2. Other information

Bulk density : 600 - 1500 kg/m<sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

calcium hydroxide (1305-62-0)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	> 2500 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male / female, Experimental value, Dermal)

Skin corrosion/irritation	: Causes skin irritation. pH: 11 - 13 Saturated solution
Serious eye damage/irritation	: Causes serious eye damage. pH: 11 - 13 Saturated solution
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

## SECTION 12: Ecological information

### 12.1. Toxicity

Portland cement (65997-15-1)	
LC50 fish 1	> 1000 mg/l (96 h, Pisces)

calcium hydroxide (1305-62-0)	
LC50 fish 1	50,6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	49,1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h algae (1)	184,57 mg/l (OECD 201: Alga, Growth Inhibition Test, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)

# Rotkalk Filz 05

## Safety Data Sheet



according to Regulation (EU) 2015/830

### 12.2. Persistence and degradability

Portland cement (65997-15-1)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

calcium hydroxide (1305-62-0)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

### 12.3. Bioaccumulative potential

Portland cement (65997-15-1)	
Bioaccumulative potential	Bioaccumulation: not applicable.

calcium hydroxide (1305-62-0)	
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

Portland cement (65997-15-1)	
Ecology - soil	No (test)data on mobility of the substance available.

calcium hydroxide (1305-62-0)	
Ecology - soil	Adsorbs into the soil.

### 12.5. Results of PBT and vPvB assessment

Component	
Portland cement (65997-15-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
calcium hydroxide (1305-62-0)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW) code : 17 09 03\* - other construction and demolition wastes (including mixed wastes) containing dangerous substances

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.2. UN proper shipping name</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.3. Transport hazard class(es)</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

# Rotkalk Filz 05

## Safety Data Sheet



according to Regulation (EU) 2015/830

ADR	IMDG	IATA	ADN	RID
<b>14.5. Environmental hazards</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

### 14.6. Special precautions for user

#### - Overland transport

Not applicable

#### - Transport by sea

Not applicable

#### - Air transport

Not applicable

#### - Inland waterway transport

Not applicable

#### - Rail transport

Not applicable

### 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

## SECTION 16: Other information

This safety data sheet replaces the previous version of 2015/5/6. The following changes were made:

Other information

: Technical information service (see point 1):

A call to Knauf Direkt will be charged at 0.39 € per minute. Callers, the telephone numbers of whom are not saved in the Knauf Gips KG address database, e.g. private property owners or noncustomers, will pay 1.69 € per minute from the German network. Callers using mobile telephones will be charged according to the network provider and tariff.

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Knauf SDS EU (REACH Annex II)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*