

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Issue date: 2022/11/7 Revision date: 2022/11/7 Supersedes version of: 2019/6/4 Version: 4.0



### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Product name : Flex-Fugenmörtel  
Product code : 11803\_0010

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Consumer use. Professional use.  
Use of the substance/mixture : Grouting Compounds

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

Knauf Gips KG  
Am Bahnhof, 7  
DE- 97346 Iphofen – Bayern  
Germany  
T +49 9323/31-0 - F +49 9323/31-277  
[zentrale@knauf.de](mailto:zentrale@knauf.de) - [www.knauf.de](http://www.knauf.de)  
E-mail address of competent person responsible for the SDS : [sds-info@knauf.com](mailto:sds-info@knauf.com)

##### Technical information

Technical information service  
T +49 (0)9001/31-2000 (see section 16)  
[knauf-direkt@knauf.de](mailto:knauf-direkt@knauf.de)

#### 1.4. Emergency telephone number

No additional information available

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H335

Full text of hazard classes, H- and EUH-statements: see section 16

##### Adverse physicochemical, human health and environmental effects

Whirled up dust may cause respiratory irritation. Mortar mixed with water becomes a strong alkaline solution. Due to the high alkalinity, the final mixture can cause skin and eye irritation. Additional mechanical influences (e.g. kneel in the wet mortar) may aggravate the skin irritation.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP) : Danger  
Contains : Portland cement

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H315 - Causes skin irritation. H318 - Causes serious eye damage. H335 - May cause respiratory irritation.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P280 - Wear protective gloves, protective clothing, eye protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a doctor, a POISON CENTER. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P261 - Avoid breathing dust. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P501 - Dispose of container to an approved waste disposal plant.
Extra phrases	: In case of proper storage in a dry location low in chromate content for at least 12 months from date of manufacture.

### 2.3. Other hazards

Other hazards which do not result in classification	: Product contains chromate reducing agent. Therefore, the cement/binder contains less than 0.0002% of water-soluble Chromium(VI). If the storage conditions are not appropriate (exposure to humidity) or the storage period is exceeded, the effectiveness of the present reducing agent can be diminished prematurely, and the cement/binder can become skin sensitizing (H317 or EUH203, respectively).
---	---

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
quartz, conc respirable crystalline silica <1% (14808-60-7)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Portland cement (65997-15-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
quartz, conc respirable crystalline silica <1% substance with a Community workplace exposure limit	CAS-No.: 14808-60-7 EC-No.: 238-878-4	< 80	Not classified
Portland cement	CAS-No.: 65997-15-1 EC-No.: 266-043-4	< 30	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Comments : Low in chromate according to EU-Regulation 1907/2006 (REACH).

Full text of H- and EUH-statements: see section 16

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Protective equipment emergency responders. Not required.
First-aid measures after inhalation	: In case of irritation or coughing : Move the affected person away from the contaminated area and into the fresh air. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Rinse and then wash skin thoroughly with water and soap. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Rinse mouth out with water. Drink plenty of water. Get medical advice/attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation, cough, shortness of breath.
Symptoms/effects after skin contact	: Repeated or prolonged contact may cause skin irritation.
Symptoms/effects after eye contact	: May cause severe irritation. Risk of serious permanent damages to eyes if the product is not rapidly removed.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: The product is not flammable.
------------------------------	---------------------------------

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Non combustible. Non oxidizing.
Explosion hazard	: Product is not explosive.

#### 5.3. Advice for firefighters

Firefighting instructions	: No specific fire-fighting instructions required.
---------------------------	--

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment. See Section 8. Precautions for safe handling. See Section 7.
Measures in case of dust release	: In case of dust production: keep upwind.

##### 6.1.2. For emergency responders

Protective equipment	: Use personal protective equipment as required. Breathing apparatus needed only when dust is formed.
----------------------	---

#### 6.2. Environmental precautions

Do not allow to enter drains or water courses.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up	: Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Do not use compressed air for cleaning.
-------------------------	---

#### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Additional hazards when processed : Not expected to present a significant hazard under anticipated conditions of normal use.
- Precautions for safe handling : Provide adequate ventilation to minimize dust and/or vapour concentrations. Use personal protective equipment as required. When using open mixing tub fill it with water first, then sprinkle the dry mortar in carefully. Keep height of fall low. Start up stirrer slowly.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Does not require any specific or particular technical measures.
- Storage conditions : Store in dry protected location to prevent any moisture contact. Store in original container. Do not store in aluminium, galvanized or other corrodable containers.
- Packaging materials : The mixture is low in chromate, because the content of sensitizing chromium (VI) is reduced by additives to below 2 ppm in the cement portion of the mortar. Prerequisite for the effectiveness of the chromate reduction is the proper storage and observance of the expiration date.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

quartz, conc respirable crystalline silica<1% (14808-60-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Silica crystalline (Quartz)
IOEL TWA	0,1 mg/m <sup>3</sup> (Respirable fraction)
Remark	(Year of adoption 2003)
Regulatory reference	SCOEL Recommendations

##### 8.1.2. Recommended monitoring procedures

No additional information available

##### 8.1.3. Air contaminants formed

No additional information available

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.1.4. DNEL and PNEC

ANNEX\_XVII\_47.\_RESTR

: 1.Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.

2.If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.

3.By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.

4. The standard adopted by the European Committee for Standardization (CEN) for testing the water-soluble chromium (VI) content of cement and cement-containing mixtures shall be used as the test method for demonstrating conformity with paragraph 1.

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Provide adequate ventilation to minimize dust concentrations.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

In case of dust production: protective goggles. Use eye protection according to EN 166, designed to protect against dusts.

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Observe skin protection plan. Apply skin care products, in particular after work.

##### Hand protection:

Wear waterproof, abrasion and alkali-resistant gloves. Investigations have proven that nitrile impregnated cotton gloves (layer thickness of about 0.15 mm) provide sufficient protection over a period of 480 minutes.

##### Other skin protection

##### Materials for protective clothing:

Long sleeved protective clothing. Impervious footwear must be worn

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. (FFP1). (FFP2). (FFP3). Filtering Half-face mask (DIN EN 149)

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid creating or spreading dust. Heavy dust production, requiring special system to control the emission of particles. Before neutralisation the alkalinity of the product may represent a danger to aquatic organisms. Do not allow into drains or water courses.

#### Consumer exposure controls:

The substance is not classified for human health hazards or for environment effects and it is not PBT or vPvB so that no exposure assessment or risk characterisation is required. For tasks where the intervention of workers is required, the substance must be handled in accordance with good industrial hygiene and safety procedures.

#### Other information:

Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: According to product specification.
Appearance	: Powder.
Odour	: odourless.
Odour threshold	: Not available
Melting point	: > 1350 °C Not determined
Freezing point	: Not applicable.
Boiling point	: Not specifically applicable
Flammability	: Not flammable
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing.
Explosive limits	: Not applicable
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: Not applicable.
Auto-ignition temperature	: Not self-igniting
Decomposition temperature	: Does not decompose when used for intended uses
pH	: 10 – 12,5
pH solution	: ≈ 10 g/l
Viscosity, kinematic	: Not applicable
Solubility	: Water: ≈ 3 g/l
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not applicable
Particle size	: Not available
Particle size distribution	: Not available
Particle shape	: Not available
Particle aspect ratio	: Not available
Particle aggregation state	: Not available
Particle agglomeration state	: Not available
Particle specific surface area	: Not available
Particle dustiness	: Not available

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

Bulk density : 900 – 1600 kg/m<sup>3</sup>

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Reacts with water.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

#### 10.4. Conditions to avoid

Keep container tightly closed to prevent moisture pick-up. Don ' use packaging made out of aluminium, zinc or tin.

#### 10.5. Incompatible materials

Reacts with (some) acids. Reacts with (some) metals and their compounds. Avoid aluminium, magnesium and zinc. ammonium salts.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation. pH: 10 – 12,5
Serious eye damage/irritation	: Causes serious eye damage. pH: 10 – 12,5
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

#### quartz, conc respirable crystalline silica<1% (14808-60-7)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause respiratory irritation.

#### Portland cement (65997-15-1)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

STOT-repeated exposure	: Long-term exposure to respirable cement dust above the occupational exposure limit may cause coughing, shortness of breath and chronic obstructive changes in the respiratory tract. No chronic effects have been observed at low concentrations. (Conclusive but not sufficient for classification)
Aspiration hazard	: Not classified

#### 11.2. Information on other hazards

No additional information available

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 12: Ecological information

#### 12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

#### Portland cement (65997-15-1)

LC50 - Fish [1] > 1000 mg/l (96 h, Pisces)

#### 12.2. Persistence and degradability

#### quartz, conc respirable crystalline silica<1% (14808-60-7)

Persistence and degradability Biodegradability: not applicable. No (test)data on mobility of the substance available.

Chemical oxygen demand (COD) Not applicable

ThOD Not applicable

#### Portland cement (65997-15-1)

Persistence and degradability Biodegradability: not applicable.

Chemical oxygen demand (COD) Not applicable (inorganic)

ThOD Not applicable (inorganic)

BOD (% of ThOD) Not applicable

#### 12.3. Bioaccumulative potential

#### quartz, conc respirable crystalline silica<1% (14808-60-7)

Bioaccumulative potential No bioaccumulation data available.

#### Portland cement (65997-15-1)

Bioaccumulative potential No bioaccumulation data available.

#### 12.4. Mobility in soil

#### quartz, conc respirable crystalline silica<1% (14808-60-7)

Surface tension No data available in the literature

Ecology - soil Low potential for mobility in soil.

#### Portland cement (65997-15-1)

Surface tension No data available in the literature

Ecology - soil No (test)data on mobility of the substance available.

#### 12.5. Results of PBT and vPvB assessment

#### Flex-Fugenmörtel

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

No additional information available



# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Mechanically recover the product. Recycle product or dispose safely.
Sewage disposal recommendations	: Do not allow into drains or water courses.
Product/Packaging disposal recommendations	: Empty remaining contents. Entrust the thoroughly decontaminated packaging to a licensed waste-contractor.
European List of Waste (LoW) code	: 17 09 04 - mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

#### 14.1. UN number or ID number

UN-No. (ADR)	: Not applicable
UN-No. (IMDG)	: Not applicable
UN-No. (IATA)	: Not applicable
UN-No. (ADN)	: Not applicable
UN-No. (RID)	: Not applicable

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR)	: Not applicable
Proper Shipping Name (IMDG)	: Not applicable
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: Not applicable
Proper Shipping Name (RID)	: Not applicable

#### 14.3. Transport hazard class(es)

##### ADR

Transport hazard class(es) (ADR) : Not applicable

##### IMDG

Transport hazard class(es) (IMDG) : Not applicable

##### IATA

Transport hazard class(es) (IATA) : Not applicable

##### ADN

Transport hazard class(es) (ADN) : Not applicable

##### RID

Transport hazard class(es) (RID) : Not applicable

#### 14.4. Packing group

Packing group (ADR)	: Not applicable
Packing group (IMDG)	: Not applicable
Packing group (IATA)	: Not applicable
Packing group (ADN)	: Not applicable
Packing group (RID)	: Not applicable

#### 14.5. Environmental hazards

Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### 14.6. Special precautions for user

#### Overland transport

Not applicable

#### Transport by sea

Not applicable

#### Air transport

Not applicable

#### Inland waterway transport

Not applicable

#### Rail transport

Not applicable

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Other information, restriction and prohibition regulations : ANNEX\_XVII\_47.\_RESTR: 1.Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.

2.If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.

3.By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.

4. The standard adopted by the European Committee for Standardization (CEN) for testing the water-soluble chromium (VI) content of cement and cement-containing mixtures shall be used as the test method for demonstrating conformity with paragraph 1.

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

#### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No additional information available

# Flex-Fugenmörtel

## Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

### SECTION 16: Other information

Other information

: Technical information service (see point 1):

A call to Knauf Direkt will be charged at 0.39 € per minute. Callers, the telephone numbers of whom are not saved in the Knauf Gips KG address database, e.g. private property owners or noncustomers, will pay 1.69 € per minute from the German network. Callers using mobile telephones will be charged according to the network provider and tariff.

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Knauf SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.